



ORCCT-F52-120822

Electronic features



Technical parameters


LED Type	2835 Honglitronic
LED/m	120 (60+60)
Voltage range	24V
Max power (24.0V)	14,4 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	120mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +50°C
Max led temperature	75°C
IP rate	IP20
Emitting angle	120°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
2600-6500K (CCT)	CRI Ra>80			1725	133	F

Dimensions



Specifications

PCB width	10 mm
Led strip height	1,5 mm
Cutting unit 24V	100 mm (6+6 led)
LED Pitch	16,66 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORCCT-F52-120822

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacture r No.	Input voltage	Misc.
OR	CCT	F	5	2	120	8	2	2	

Packaging

Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	85 g
Gross weight	130 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

