

ORYEL-F52-060811

Electronic features



www.orizzonteled.com
info@orizzonteled.com




Technical parameters

LED Type	2835
LED/m	60
Voltage range	12V
Max power (24.0V)	14,4 W/m
Useful life span	50000h
Operating current (single LED)	60mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	80°C
IP rate	IP20
Emitting angle	120°

Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
590-595nm (YEL)				280	22	

Dimensions



Specifications

PCB width	10 mm
Led strip height	1,5 mm
Cutting unit 12V	50 mm (3 led)
LED Pitch	16,67 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm ²

ORYEL-F52-060811

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	YEL	F	5	2	060	8	1	1	

Packaging

Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	80 g
Gross weight	125 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

