



ORxxx-F32-060820

Electronic features




Technical parameters	
LED Type	2835 Honglitronic
LED/m	60
Voltage range	5V
Max power (24.0V)	5,5 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	18mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +50°C
Max led temperature	75°C
IP rate	IP20
Emitting angle	120°



Lighting parameters						
CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K 3step (30s)	CRI Ra>80	81	97	460	93	F
4000K 3step (40s)	CRI Ra>80	80	92	450	91	G
6000-6500K (600)	CRI Ra>80	81	93	475	96	F

Dimensions



Specifications	
PCB width	5 mm
Led strip height	1,5 mm
Cutting unit 5V	16,7 mm (1 led)
LED Pitch	16,7 mm
Reel length	3 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm ²

ORxxx-F32-060820

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	30s	F	3	2	060	8	2	0	
OR	40s	F	3	2	060	8	2	0	
OR	600	F	3	2	060	8	2	0	

Packaging

Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	20 g
Gross weight	50 g



3 meters per carton roll



1 roll per carton box

150 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

