

# ORxxx-F52-120811-W5

## Electronic features



2835

IP20

12V



[www.orizzonteled.com](http://www.orizzonteled.com)

[info@orizzonteled.com](mailto:info@orizzonteled.com)




### Technical parameters

LED Type	2835 Honglitronic
LED/m	120
Voltage range	12V
Max power (24.0V)	10 W/m
Useful life span	50000h
Operating current (single LED)	21mA
Copper thickness	105 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	75°C
IP rate	IP20
Emitting angle	120°

### Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
460-465nm (BLU)				200	22	
605-615nm (ORA)				200	22	

## Dimensions



### Specifications

PCB width	5 mm
Led strip height	1,5 mm
Cutting unit 12V	25 mm (3 led)
LED Pitch	8,33 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,5 mm <sup>2</sup>

# ORxxx-F52-120811-W5

## Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	BLU	F	5	2	120	8	1	1	-W5
OR	ORA	F	5	2	120	8	1	1	-W5

## Packaging

### Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	45 g
Gross weight	75 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

## Certifications

