



# ORxxx-F52-1208F1-W5

## Electronic features



### Technical parameters


LED Type	2835
LED/m	120
Voltage range	12V
Max power (24.0V)	10 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	21mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +50°C
Max led temperature	70°C
IP rate	IP20
Emitting angle	120°



### Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
2700K 3step (27s)	CRI Ra>80	82	94	960	107	F
3000K 3step (30s)	CRI Ra>80	80	93	1060	118	F
4000K 3step (40s)	CRI Ra>80	81	95	1130	126	E
6500K 3 step (65s)	CRI Ra>80	80	93	1120	124	E

## Dimensions



### Specifications

PCB width	5 mm
Led strip height	1,5 mm
Cutting unit 12V	25 mm (3 led)
LED Pitch	8,33 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,5 mm²

# ORxxx-F52-1208F1-W5

## Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	27s	F	5	2	120	8	F	1	-W5
OR	30s	F	5	2	120	8	F	1	-W5
OR	40s	F	5	2	120	8	F	1	-W5
OR	65s	F	5	2	120	8	F	1	-W5

## Packaging

### Technical parameters

Carton dimension	520 x 330 x 170 mm
Quantity per carton	50
Net weight	82 g
Gross weight	102 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

## Certifications

