


ORxxx-F52-1208F1/14.4

Electronic features



www.orizzonteled.com
info@orizzonteled.com




Technical parameters

LED Type	2835
LED/m	120
Voltage range	12V
Max power (24.0V)	14,4 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	60mA
Copper thickness	105 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	70°C
IP rate	IP20
Emitting angle	120°

Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3500K 3step (35s)	CRI Ra>80	80	93	1550	120	E
4000K 3step (40s)	CRI Ra>80	81	95	1624	125	E

Dimensions



Specifications

PCB width	10 mm
Led strip height	1,5 mm
Cutting unit 12V	25 mm (6 led)
LED Pitch	8,33 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm ²

ORxxx-F52-1208F1/14.4

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	35s	F	5	2	120	8	F	1	/14.4
OR	40s	F	5	2	120	8	F	1	/14.4

Packaging

Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	75 g
Gross weight	120 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

