


ORxxxF52120DN2-F

Electronic features




Technical parameters	
LED Type	2835
LED/m	120
Voltage range	24V
Max power (24.0V)	11 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	15mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	75°C
IP rate	IP20
Emitting angle	120°



Lighting parameters						
CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K 3step (30s)	CRI Ra>93	85	106	1530	155	D

Dimensions



Specifications	
PCB width	8 mm
Led strip height	2 mm
Cutting unit 24V	33,3 mm (4 led)
LED Pitch	8,33 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxxF52120DN2-F

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	30s	F	5	2	120	D	N	2	-F

Packaging

Technical parameters

Carton dimension	395 x 310 x 160 mm
Quantity per carton	50
Net weight	100 g
Gross weight	110 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

