


ORxxx-F52-240DF1

Electronic features



2835 CRI Ra>80 IP20 12V



Orizzonte
LED Lighting

www.orizzonteled.com
info@orizzonteled.com




Technical parameters

LED Type	2835
LED/m	240
Voltage range	12V
Max power (24.0V)	19,2 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	20mA
Copper thickness	105 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	70°C
IP rate	IP20
Emitting angle	120°

Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
6500K 3 step (65s)	CRI Ra>80			1900	110	F

Dimensions



Specifications

PCB width	12 mm
Led strip height	1,5 mm
Cutting unit 12V	12,5 mm (3 led)
LED Pitch	4,17 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxx-F52-240DF1

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	65s	F	5	2	240	D	F	1	

Packaging

Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	105 g
Gross weight	150 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

