


ORxxx-F52-240DZ2-S1



Orizzonte
LED Lighting

www.orizzonteled.com
info@orizzonteled.com



Technical parameters


LED Type	2835
LED/m	240
Voltage range	24V
Max power (24.0V)	22 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	23mA
Copper thickness	70 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	75°C
IP rate	IP20
Emitting angle	120°



Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K 3step (30s)	CRI Ra>80	82	95	2255	114	F

Dimensions



Specifications

PCB width	10 mm
Led strip height	1,5 mm
Cutting unit 24V	25 mm (6 led)
LED Pitch	4,17 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxx-F52-240DZ2-S1

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	30s	F	5	2	240	D	Z	2	-S1

Packaging

Technical parameters

Carton dimension	520 x 330 x 170 mm
Quantity per carton	50
Net weight	135 g
Gross weight	180 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

