



# ORxxx-F52-x1288H2/13

## Electronic features



### Technical parameters


LED Type	2835
LED/m	128
Voltage range	24V
Max power (24.0V)	13 W/m
Led color binning	3step MacAdam
Useful life span	50000h
Operating current (single LED)	34mA
Copper thickness	105 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	70°C
IP rate	IP20
Emitting angle	120°



### Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K 3step (30s)	CRI Ra>97	95	102	1500	128	E
4000K 3step (40s)	CRI Ra>97	95	101	1560	133	E

## Dimensions



### Specifications

PCB width	8 mm
Led strip height	1,5 mm
Cutting unit 24V	62,5 mm (8 led)
LED Pitch	7,81 mm
Reel length	5 m
Adhesive tape	3M 9495LE
Cable cross-section	0,75 mm <sup>2</sup>

# ORxxx-F52-x1288H2/13

## Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	30s	F	5	2	x12	8	8	H	2/13
OR	40s	F	5	2	x12	8	8	H	2/13

## Packaging

### Technical parameters

Carton dimension	520 x 170 x 330 mm
Quantity per carton	50
Net weight	70 g
Gross weight	115 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

## Certifications

