



ORxxx-K52-400R2-W5

Electronic features



www.orizzonteled.com
info@orizzonteled.com




Technical parameters

LED Type	0620
LED/m	400
Voltage range	24V
Max power (24.0V)	11 W/m
Led color binning	5step MacAdam
Useful life span	20000h
Operating current (single LED)	9mA
Copper thickness	108 µm
Operating temperature	-10°C ~ +45°C
Max led temperature	65°C
IP rate	<u>IP65</u>
Emitting angle	140°

Lighting parameters

CCT	CRI	Rf	Rg	Lm/m	Lm/W	Energy rating
3000K (300)	CRI Ra>90	96	104	790	80	G

Dimensions



Specifications

PCB width	7 mm
Led strip height	3 mm
Cutting unit 24V	20 mm (8 led)
LED Pitch	4 mm
Reel length	5 m
Adhesive tape	<u>3M 9495LE</u>
Cable cross-section	0,75 mm ²

ORxxx-K52-400R2-W5

Product Range

Version	Temperature	IP type	Strip length	PCB colour	Led/m	LED type	Manufacturer No.	Input voltage	Misc.
OR	300	K	5	2	400	O	R	2	-W5

Packaging

Technical parameters

Carton dimension	300 x 250 x 200 mm
Quantity per carton	50
Net weight	195 g
Gross weight	235 g



5 meters per carton roll



1 roll per carton box

250 m per carton

Orizzonte uses paper boxes and reels for its LED strips to fight for a plastic free world.

Certifications

